

MCP900

The MCP900 is a stylish easy-to-install manual call point, is it ideal for internal environments that require manual activation and inhibition of fire alarms and fire extinguishments systems.

It is also suitable for door and escalator control and is available in a choice of colours. It can be mounted in a custom surface mounting back box or flush mounted to the majority of outlet box formats available in europe.

The MCP900 manual call point can be activated by pushing the centre of the operating face (black arrows indicate the exact point), and reset by means of the special key (without glass replacement). A special version of the MCP900 provides local led indication of stand by or alarm status.

The product is supplies complete with surface mount.



ORDER CODES

MCP900RCS	Conventional, restorable call point with alarm LED and choice serie resistor. Complete with restore key.
MCP900RCB	Conventional, restorable, call point with alarm LED. Complete with restore key.
MCP900/RS	Restorable, call point with free voltage changeover contact. Complete with restore key.
MCP900/RV	Addressable, restorable call point. Complete with restore key.
MCP900/RF	Frames (10 pcs).
MCP900/LN	Lexan language dependent (10 pcs).
MCP900/DN	Security protection (10 pcs).
MCP900/RK	Restore key (10 pcs).

CALL-R24

Self-Powered siren.

- High performance siren
- Modulated frequency sound emission
- Supplementary interior protection in metal, resistant to corrosive agents
- Flasher cutout on low battery
- Separate controls for acoustic and flasher signalling
- Control voltage 27.6 Vdc
- Battery compartment: up to 12 V 6.5 Ah
- Sound level: 104 dBA (3 mt.)
- Carrier frequency: 1750 Hz
- Temperature range: -25 ÷ +55 °C - IP 34
- Dimensions (wxhxd): 180x270x90 mm
- Weight (without battery): 2,8 Kg



ORDER CODES

CALL-R24	Self-Powered siren
-----------------	--------------------